

WL Cube Firewall™

First class purification performance in a distinct compact unit



Standard model

Excellent, thoroughly purified water for small workplaces

With its sophisticated and premium look, the WL Cube Firewall (WL Cube FW) is the ideal worktop solution for small working environments, meeting rooms, kitchens, bar and break areas.

Advanced technology

The WL Cube FW features three core technologies:



High performance filtration

Waterlogic's filters are certified to stringent standards, carrying the Water Quality Association's Gold Seal of approval, meaning they offer the best possible filtration.



Firewall

Waterlogic's patented Firewall technology utilises a highly effective UVC purification system at the point of dispense. Firewall guarantees 99.9999% purified water. Glass after glass.



BioCote® protection

The WL Cube FW key surfaces are infused with BioCote, a silver ion additive able to inhibit microbial growth on the surface of the products helping to reduce unpleasant odours, degradation of key surfaces and the potential for cross contamination.

Expert purification

Featuring Firewall, which thoroughly purifies the water as it is dispensed, acting also as a barrier preventing back contamination from outside, the WL Cube FW is the only compact machine on the market delivering totally safe cold, ambient and sparkling water, cleansed from pathogens by up to 99.9999%.

Features

Firewall, patented UV technology reduces the risks of bacteria, viruses, and cysts purifying the water up to 99.9999%, 100% of the time

Removable drip tray to easily accommodate average size sport bottles







Elegant touch sensitive control panel for ease of use

Energy saving sleep mode to reduce power consumption when unit is not in use

LED UV fault indicator for easier servicing and peace of mind

BioCote® protected dispensing area

Water options

	cold	sparkling	ambient	hot	extra hot
1					
2					

Number of users



Technical specifications

Types available

Countertop

Dimensions

Standard model

Cube: 296mm/11.6" (W) x 375mm/14.8" (H) x 425mm/16.7" (D)

Dispensing area height

155mm/6.10" (with drip tray)

247mm/9.7" (without drip tray)

Weight

Standard model: 18 KG/ ~39 lbs

Standard filtration supplied

Carbon

Storage capacity

Standard model:

Cold tank 1.4 litre. Hot tank 1.3 litre

Water temperatures settings

Cold 5-15°C / 41-59°F

Hot 87-95°C / 188.6-203°F



Sparkling model

Tested and certified

NSF/ANSI-55 Class A
Ultrapure Microbiological
Water Treatment Systems
NSF P231
Protocol for
Microbiological Purifiers



*certificate may vary depending on different models or products

Distribué par

SERDIM DISTRIBUTION

Immeuble Serdim – ZI La Lézarde – 97232 Lamentin

Tél 0596 57 29 21 – Fax 0596 51 83 64