

### Minimise Your Waste Maximise Your Savings

# CS3 Static Waste Compactor

#### Specification

Our CS3 static compactors are mainly used for dry general waste i.e. general office waste, broken pallets, furniture, window frames, textiles, etc.

With fast cycle time, high volume charge box, heavy duty

compaction and low noise levels, our static waste compactors are the perfect choice to minimise your waste costs. Available in a range of colours, with clear operating instructions and health and safety stickers as standard. Easy to operate, safe to use and backed by a network of our own engineers to ensure maximum reliability.



#### **Technical Information**

Compaction Force	27 Tonnes
Power Requirement	32A 3Ph + N + E Socket outlet fused at 32Amp D type with local 30 Milliamp RCD protection (If you have an existing supply that doesn't match this specification, please contact technical@capitalcompactors.co.uk to check if it's usable or discuss a solution)
Motor	7.5kW
Noise Level	70dB at 3m From Unit
Cycle Time	45 Seconds
Charge Box Volume	2.29m <sup>3</sup>
Volume Per Stroke	2.00m <sup>3</sup>
Ram Depth	700mm
Ram Diameter	150mm
Running Hydraulic Pressure	2000psi
Pinning Hydraulic Pressure	2150psi
Overall Length	3406mm (+1095mm Rear Dock Plate)
Overall Width	1645mm
Overall Height	2782mm
Variant Shown	Rear Dock Loading Hopper

The details provided in our specification sheets are for your general information and use only. They are subject to change due to the continual design and build development.

#### **Capital Compactors**

Capital House, 26 Sudley Road, Bognor Regis, West Sussex PO21 1ER

www.capitalcompactors.co.uk

call +44 (0)1243 837614 fax +44 (0)1243 837615 email enquiries@capitalcompactors.co.uk











## Minimise Your Waste **Maximise Your Savings**

