



CEILING & FLOOR



















SPECIFICATIONS

3 years warranty on spare parts and compressors



Ceiling & Floor

Ceiling & Floor Specification_R410A 3D DC Inverter

Standard Feature	Optional Feature
 Front Desk Control  ZigB Design  Twin Combination  Sleep Mode  3D Air Flow  Refrigerant Leakage Detect  Louver Position Memory  Anti-flicker  Timer  Low Ambient Cooling  Emergency Using  Fresh Air	 Inverter Engine Mode  Follow Me  B/C Heating  Wind Control  Central Control Management  Built-in Drain Pump

Specification				MUE-18HRFNX-QRD0	MUE-24HRFNX-QRD0	MUE-36HRFNX-QRD0	MUE-36HRFNX-QRD0
Model NO.	Indoor Unit	Outdoor Unit		MOB30U-18HFN1-QRD0	MCA30U-24HFN1-QRD0	MOD30U-36HFN1-QRD0	MOD30U-36HFN1-RRD0
Performance							
Power Supply			V-,Hz,Ph	220-240V- 50Hz, 1Ph	220-240V- 50Hz, 1Ph	220-240V- 50Hz, 1Ph	380-420V- 50Hz, 3Ph
Cooling Capacity			Btu/h	17700(2700-21000)	22500(4100-28000)	36000(10000-41000)	36000(10000-41000)
			kW	5.2(0.79-6.15)	6.6(1.20-8.21)	10.5(2.93-12.02)	10.5(2.93-12.02)
Heating Capacity			Btu/h	19000(3000-24000)	24000(4100-29500)	37900(9000-45000)	37900(9000-45000)
			kW	5.67(0.88-7.03)	7.03(1.20-8.65)	11.1(2.64-13.19)	11.1(2.64-13.19)
SEER			W/W	6.5	6.1	6.1	6.1
Cooling Energy Rate				A++	A++	A++	A++
SCOP	Avg./Warm/Cold	W/W		4.0/5.1/-	4.0/5.1/-	4.0/5.1/-	4.0/5.1/-
Heating Energy Rate	Avg./Warm/Cold			A+/A+++/-	A+/A+++/-	A+/A+++/-	A+/A+++/-
Air Flow Volum	Indoor	H/M/L	m3/h	902/786/677	1208/1066/853	2160/1844/1431	2160/1844/1431
Sound Pressure Noise Level	Indoor	H/M/L	dB(A)	45/40/37	50/46/41	51/47/42	51/47/42
	Outdoor		dB(A)	57	61	61	62
Sound Power Noise Level	Indoor		dB(A)	60	65	65	65
	Outdoor		dB(A)	65	66	70	70
Dimension & Weight							
Net Dimension	Indoor	WxDxH	mm	1068x675x235	1068x675x235	1650x675x235	1650x675x235
	Outdoor	WxDxH	mm	800x333x554	845x363x702	946x410x810	946x410x810
Packing Dimension	Indoor	WxDxH	mm	1145x755x313	1145x755x313	1725x755x313	1725x755x313
	Outdoor	WxDxH	mm	920x390x615	965x395x755	1090x500x865	1090x500x865
Net/Gross Weight	Indoor		Kg	26.6/31.8	26.8/31.9	39/45	39/45
	Outdoor		Kg	35.5/38.4	49/51.5	67.2/72.9	78.9/83.9
Stuffing Quantity							
	Indoor	20'/40'/40'HQ	Unit	102/220/252	102/220/252	72/147/167	72/147/167
	Outdoor	20'/40'/40'HQ	Unit	108/219/292	102/216/216	44/96/144	44/96/144

Ceiling & Floor Specification_R410A 3D DC Inverter

Standard Feature



Optional Feature



Specification				MUE-48HRFNX-QRD0	MUE-48HRFNX-QRD0	MUE-55HRFNX-QRD0
Model NO.	Indoor Unit	Outdoor Unit		MOE30U-48HFN1-QRD0	MOE30U-48HFN1-RRD0	MOE30U-55HFN1-RRD0
Performance						
Power Supply			V~,Hz,Ph	220-240V~ 50Hz, 1Ph	380-415V~ 50Hz, 3Ph	380-415V~ 50Hz, 3Ph
Cooling Capacity			Btu/h	46700(14000-56000)	48000(14000-56000)	53900(17000-61800)
			kW	13.7(4.10-16.41)	14.0(4.10-16.41)	15.8(4.98-18.11)
Heating Capacity			Btu/h	54600(15000-63000)	55600(15000-63000)	61000(18000-70000)
			kW	16.0(4.40-18.46)	16.3(4.40-18.46)	17.9(5.28-20.51)
SEER			W/W	6,1	6,1	6,1
Cooling Energy Rate				A++	A++	A++
SCOP	Avg./Warm/Cold		W/W	4.0/5.1/-	4.0/5.1/-	4.0/5.1/-
Heating Energy Rate	Avg./Warm/Cold			A+/A+++/-	A+/A+++/-	A+/A+++/-
Air Flow Volum	Indoor	H/M/L	m3/h	2329/1930/1417	2329/1930/1417	2454/1834/1426
Sound Pressure Noise Level	Indoor	H/M/L	dB(A)	54/50/46	54/50/46	54/47/42
	Outdoor		dB(A)	65	65	63
Sound Power Noise Level	Indoor		dB(A)	72	72	72
	Outdoor		dB(A)	73	73	77
Dimension & Weight						
Net Dimension	Indoor	WxDxH	mm	1650x675x235	1650x675x235	1650x675x235
	Outdoor	WxDxH	mm	952x410x1333	952x410x1333	952x410x1333
Packing Dimension	Indoor	WxDxH	mm	1725x755x313	1725x755x313	1725x755x313
	Outdoor	WxDxH	mm	1095x500x1470	1095x500x1470	1095x500x1470
Net/Gross Weight	Indoor		Kg	41.2/47.6	41.2/47.6	41.4/47.8
	Outdoor		Kg	95.1/108.4	108.1/121.2	112.8/126
Stuffing Quantity						
	Indoor	20'/40'/40'HQ	Unit	72/147/167	72/147/167	72/147/167
	Outdoor	20'/40'/40'HQ	Unit	22/46/46	22/46/46	22/46/46